

# CLASSIC SERIES POWER CONDITIONERS (15 AMP)



Furman brings together superior protection and outstanding performance in a sturdy, rack-mountable design. Classic Series Power Conditioners feature Series Multi-Stage Protection (SMP), Linear Filtering Technology (LiFT), Extreme Voltage Shutdown (EVS), and offer a new industrial design and full feature set engineered specifically for the A/V professional.



## PL-8 C FEATURES



## PL-PLUS C FEATURES



## PL-PLUS DMC FEATURES




# FURMAN®


WWW.FURMANSOUND.COM

# THE POWER OF **FURMAN** TECHNOLOGY


ALL CLASSIC MODELS FEATURE



DUAL SMOOTH TRACK RETRACTABLE LED LIGHTS  
ILLUMINATE EQUIPMENT IN YOUR RACK




ISOLATED OUTLET BANKS MINIMIZE  
INTER-COMPONENT INTERFERENCE  
AND NOISE CONTAMINATION



REAR PANEL BNC CONNECTOR POWERS  
ANY STANDARD GOOSENECK LAMP  
FOR REAR RACK ILLUMINATION




FURMAN'S EXCLUSIVE SMP TECHNOLOGY  
PROVIDES THE HIGHEST LEVEL OF SURGE &  
SPIKE PROTECTION AVAILABLE



NINE TOTAL OUTLETS (8 REAR PANEL OUTLETS  
AND ONE FRONT PANEL CONVENIENCE OUTLET)

ADDITIONAL PL-PLUS C FEATURES:




SEGMENTED LED VOLTMETER MONITORS AND  
DISPLAYS INCOMING LINE VOLTAGE



LED STATUS INDICATORS WARN YOU WHEN  
VOLTAGE IS OUTSIDE OF NOMINAL RANGE OR  
WHEN PROTECTION HAS BEEN COMPROMISED



THREE WIDELY SPACED OUTLETS ACCOMMODATE  
BULKY AC POWER TRANSFORMERS



LIFT OFFERS LINEAR AC POWER FILTERING TO  
ENSURE CLEAN POWER FOR UNEQUALLED  
AUDIO & VIDEO CLARITY




ADVANCED EVS CIRCUITRY DETECTS DANGEROUS VOLTAGE  
IRREGULARITIES AND SAFELY POWERS DOWN ITSELF AND  
CONNECTED EQUIPMENT IN UNSAFE CONDITIONS



15 AMP RATING FEATURING A HIGH INRUSH THER-  
MAL CIRCUIT BREAKER FOR ADDED PROTECTION

ADDITIONAL PL-PLUS DMC FEATURES:



LARGE DIGITAL VOLTMETER/AMMETER WITH  
DISCRETE DIMMER BUTTON DISPLAYS LINE  
VOLTAGE AND TRUE RMS CURRENT DRAW

## CLASSIC SERIES REAR PANEL (ALL 15AMP MODELS)



## CLASSIC SERIES SPECIFICATIONS

MAXIMUM OUTPUT CURRENT:  
15 AMPS

LINE CORD:  
CAPTIVE 3/14 AWG, 10 FT BLACK CORD WITH NEMA 15 PLUG

PULL OUT LIGHTS:  
TWO MULTI-LED, DIMMABLE LAMPS

BNC SOCKET W/SWITCH:  
REAR RACK LAMP, 12VAC 500MA MAX (LAMP NOT INCLUDED)

OPERATING VOLTAGE:  
90 TO 139 VAC

OVER VOLTAGE SHUTDOWN:  
140 VAC NOMINAL

SPIKE PROTECTION MODES:  
LINE TO NEUTRAL, ZERO GROUND LEAKAGE

SPIKE CLAMPING VOLTAGE:  
188 VAC PEAK @3,000 AMPS

RESPONSE TIME:  
1 NANOSECOND

MAXIMUM SURGE CURRENT:  
6,500 AMPS

NOISE ATTENUATION:  
10 DB @ 10KHZ, 40 DB @ 100KHZ, 50 DB @500 KHZ

DIMENSIONS:  
19" W x 10.5" D x 1.75" H

WEIGHT:  
12 LBS.

POWER CONSUMPTION:  
12 WATTS