Wireless Essentials® Accessory Microphones and Input Cables

For all Audio-Technica UniPak™ Wireless Systems

WIRELESS LAVALIER MICROPHONES

AT829cW Cardioid Condenser Wireless Lavalier Microphone

AT831cW Cardioid Condenser Wireless Lavalier Microphone

MT830cW Omni Condenser Wireless Lavalier Microphone

MT830cW-TH Omni Condenser Wireless Lavalier Microphone (beige color)

 For professional business presentations, public speaking, theater performances

Operation: These microphones' small size allows them to be worn as a lavalier, or hidden in loose clothing. For normal lavalier use, attach the microphone about 6" (15 cm) below the user's chin. Anticipate movements that may cause the microphone to rub against or be covered by clothing and position the microphone to avoid it.



AT829cW

WIRELESS CLIP-ON INSTRUMENT MICROPHONES

ATM35cW Cardioid Condenser Wireless Instrument Microphone
PRO 35xcW Cardioid Condenser Wireless Instrument Microphone

- For close-miking brass, woodwinds and any hard-to-mic instruments
- UniMount® clip permits accurate positioning while protecting element

Operation: Clip directly on to instrument. The microphone is uniquely capable of picking up high-intensity sound without distortion.



ATM35cW

WIRELESS GOOSENECK MICROPHONE

U857ALcW Cardioid Condenser Wireless Gooseneck Microphone

- For high-quality sound reinforcement, professional recording and broadcasting
- Small-diameter, alternating gooseneck design permits highly flexible positioning
- Overall length of 16.58" (421.0 mm)

Operation: The microphone direct mounts to any 5/8"-27 stand, or to the included threaded mounting flange. Cable exit is from the bottom of the microphone. If necessary, the included pass-through adapter may be used to provide a side exit for the cable.



U857ALcW

WIRELESS HEADWORN MICROPHONES

ATM73cW Cardioid Condenser Wireless Headworn Microphone
ATM75cW Cardioid Condenser Wireless Headworn Microphone
PRO 8HEcW Hypercardioid Dynamic Wireless Headworn Microphone
AT889cW Noise-canceling Condenser Wireless Headworn Microphone

- Designed for professional public speaking, aerobics instruction, and other demanding applications
- Comfortable, unobtrusive headband design

Operation: After use in high-moisture applications, such as aerobics instruction, on-stage performing, etc., remove the foam screen, wipe off the headset with a towel and permit them to air-dry. (Do not store in a closed space, such as a plastic bag, until all moisture has evaporated.)

ATM73cW: Wear the headband around the back of the head with each cushioned support pad resting on the temple in front of the ear.

ATM75cW and PRO 8HEcW: Wear the headband around the back of the head with each cushioned support pad resting on the temple in front of

the ear. The assembly may be oriented so that the microphone descends from either the left or right side. The cable should remain clipped to the headband, with some slack at the boom connection.

AT889cW: Position the adjustable band around the back of the neck, placing the cushioned earpieces over each ear. Adjust the headband as necessary for a stable, comfortable fit.



ATM75cW

WIRELESS BOUNDARY MICROPHONE

U851cW Cardioid Condenser Wireless Boundary Microphone

- Designed for surface-mount applications in sound reinforcement, professional recording, broadcasting and theater performances
- Heavy die-cast case and rubber feet minimize coupling of surface vibration to the microphone
- Low-profile design for minimum visibility

Operation: The microphone should be placed on a flat, unobstructed mounting surface, with the front of the microphone facing the sound source. The sound source should not be below, or higher than 60° above, the plane of the mounting surface.



U851cW

GUITAR AND MICROPHONE CABLES

AT-GCW Guitar Input Cable

XLRW Microphone Input Cable

- Engineered for maximum signal transfer and minimum loss
- Heavy-duty construction and state-of-the-art professional connectors

Operation:

AT-GCW: Connects electric guitar, bass and other instruments with a '/4" output jack to an Audio-Technica UniPakTM body-pack transmitter.

XLRW: Connects a Lo-Z microphone with an XLRM-type output to an Audio-Technica UniPak™ body-pack transmitter.



AT-GCW

Specifications[†] WIRELESS LAVALIER MICROPHONES

AT829cW Cardioid Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Clothing clip; windscreen

Cardioid (Condenser	Wireless	Lavalier	Microphone
	Cardioid	Cardioid Condenser	Cardioid Condenser Wireless	Cardioid Condenser Wireless Lavalier

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Clothing clip; windscreen

MT830cW Omni Condenser Wireless Lavalier Microphone

	occ Editation timorophicms
Element:	Condenser
Polar Pattern:	Omnidirectional
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Clothing clip; press-on windscreens

MT830cW-TH Omni Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Omnidirectional
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Clothing clip; press-on windscreens

WIRELESS GOOSENECK MICROPHONE

U857ALcW Cardioid Condenser Wireless Gooseneck Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	29.5" (0.75 m) cable terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	AT8153 two-stage foam windscreen; AT8663 A-mount flange; AT8664 A-mount cable pass-through adapter

WIRELESS BOUNDARY MICROPHONE

U851cW Cardioid Condenser Wireless Boundary Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	29.5" (0.75 m) cable terminated for use with Audio-Technica UniPak™ body-pack transmitters

WIRELESS CLIP-ON INSTRUMENT MICROPHONES

ATM35cW Cardioid Condenser Wireless Instrument Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessory Furnished:	AT8418 UniMount® instrument mount

PRO 35xcW Cardioid Condenser Wireless Instrument Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessory Furnished:	AT8418 UniMount® instrument mount



Wireless Essentials® Accessory Microphones and Input Cables

Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224 P51828 © 2006 Audio-Technica U.S., Inc. Printed in U.S.A.

WIRELESS HEADWORN MICROPHONES

ATM73cW Cardioid Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Windscreens

ATM75cW Cardioid Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessory Furnished:	Windscreen

PRO 8HEcW Hypercardioid Dynamic Wireless Headworn Microphone

Element:	Dynamic
Polar Pattern:	Hypercardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessory Furnished:	Windscreen

AT889cW Noise-canceling Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Noise-canceling
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak™ body-pack transmitters
Accessories Furnished:	Windscreen; cable clip

GUITAR AND MICROPHONE CABLES

AT-GCW Guitar Input Cable

Length:	36" (0.9 m)
Connectors:	¹/₄" phone plug to HRS connector for use between instrument and Audio-Technica UniPak™ transmitters

XLRW Microphone Input Cable

Length:	29.5" (0.75 m)	
Connectors:	XLRF-type connector to HRS connector for use between Lo-Z microphone and Audio-Technica UniPak™ body-pack transmitters	

[†] Specifications are subject to change without notice.